

The NLR EMC test facility is one of NLR's environmental test facilities and covers the following Aerospace standards:

- DoD MIL-STD-461 (E to G) (*)
- RTCA DO-160 (D to G) (*)
- EUROCAE ED-14 (D to G) (*)
- AIRBUS ABD0100.1.2 (E and G)
- Boeing D6-16050-5 Rev. C and D6-16050-4 Rev. D
- DoD MIL-STD-704 (D to F)

(*) Performed under ISO-17025 accreditation, registration RVA L-220 'TESTING'

Other standards (e.g. FCC, IEC, DEF-STAN) and dedicated test procedures can also be supported.

Other capabilities of the NLR EMC facility are:

- Crosstalk measurements according to IEC 61935-1
- Surface transfer impedance – Triaxial method measurements according to IEC 62153-4-3
- Shielded screening attenuation measurements according to IEC 62153-4-4
- Surface transfer impedance – Line injection method measurements according to IEC 62153-4-6
- In-situ EMI test to customer specifications
- Helicopter platform annex Open Area Test Site (OATS) for emission measurements
- Variable frequency AC power source (9 kVA) for power quality tests

DoD MIL-STD-461G:

- CE101, conducted emissions, audio frequency currents, power leads, 30 Hz to 10 kHz (*)
- CE102, conducted emissions, radio frequency potential, power leads, 10 kHz to 10 MHz (*)
- CE106, conducted emissions, antenna port, 10 kHz to 40 GHz
- CS101, conducted susceptibility, power leads, 30 Hz to 150 kHz (*)
- CS114, conducted susceptibility, bulk cable injection, 10 kHz to 200 MHz (*)
- CS115, conducted susceptibility, bulk cable injection, impulse excitation
- CS116, conducted susceptibility, damped sinusoidal transients, cables and power leads, 10 kHz to 100 MHz
- CS117, conducted susceptibility, lightning induced transients, cables and power leads (*)
- CS118, personnel borne electrostatic discharge
- RE101, radiated emissions, magnetic field, 30 Hz to 100 kHz (*)
- RE102, radiated emissions, electric field, 10 kHz to 18 GHz (*)
- RS101, radiated susceptibility, magnetic field, 30 Hz to 100 kHz (*)
- RS103, radiated susceptibility, electric field, 2 MHz to 40 GHz; HIRF 10 kHz to 18 GHz, 200 V/m (*)

(*) Performed under ISO-17025 accreditation, registration RVA L-220 'TESTING'

RTCA DO-160G/EUROCAE ED-14G:

- Section 15, Magnetic Effect
- Section 16, Power Input
- Section 17, Voltage Spike
- Section 18, Audio Frequency Conducted Susceptibility (*)
- Section 19, Induced Signal Susceptibility (*)
- Section 20, Radio Frequency Susceptibility (Radiated and Conducted) (*)
- Section 21, Emission of Radio Frequency Energy (Radiated and Conducted) (*)
- Section 22, Lightning Induced Transient Susceptibility (*); Waveform 1 to 5, Level 1 to 5, Single Stroke, Multiple Stroke, Multiple Burst, PIN Injection, Cable Induction, Ground Injection

(*) Performed under ISO-17025 accreditation, registration RVA L-220 'TESTING'

AIRBUS ABD0100.1.2G:

- 3.2.2, Lightning Indirect Effects
- 3.3.2, Radio Frequency Conducted Susceptibility (10 kHz to 400 MHz)
- 3.3.3, Radio Frequency Radiated Susceptibility – Average Levels (100 MHz to 18 GHz)
- 3.3.5, RF Radio Frequency Susceptibility for Internal Transmitter environment
- 3.4.1, Magnetic Effect
- 3.4.3, Power Supply Audio Frequency Conducted Susceptibility
- 3.4.4, Induced Signal Susceptibility
- 3.4.5, Emission of Radio Frequency Energy (Radiated and Conducted)
- 3.5 Electrostatic Discharge (ESD) Susceptibility

Boeing D6-16050-4 Rev D:

- 7.2.1, AF Conducted Susceptibility – Power Inputs
- 7.2.2, AF Electric Field Susceptibility – Wiring
- 7.2.3, AF Magnetic Field Susceptibility – Wiring
- 7.2.4, AF Magnetic Field Susceptibility – Equipment
- 7.3.1, Conducted RF Susceptibility – 10 kHz to 400 MHz
- 7.3.3, Radiated RF Susceptibility Test – 100 MHz to 18 GHz
- 7.4.1, Ground-Injected Transient Susceptibility
- 7.4.2, Pin-Injected Transient Susceptibility
- 7.4.3, Interconnecting Cable Injected Transient Susceptibility
- 7.4.4, Lightning Induced Multiple-Burst Transient Susceptibility
- 7.5.2, Induced Spikes Susceptibility
- 8.3.1, AF Capacitive Coupling
- 8.3.2, AF Inductive Coupling
- 8.4.1, RF Conducted Emissions
- 8.4.2, RF Radiated Emissions

Boeing D6-16050-5 Rev C:

- 7.2.1, AF Electric Field Susceptibility – Wiring
- 7.2.2, AF Magnetic Field Susceptibility – Wiring
- 7.2.3, AF Magnetic Field Susceptibility – Equipment
- 7.3.1, Conducted RF Susceptibility – 10 kHz to 400 MHz
- 7.3.2, Radiated RF Susceptibility Test – 100 MHz to 18 GHz
- 7.5.1, Induced Spikes Susceptibility
- 8.1.1, AF Capacitive Coupling
- 8.1.2, AF Inductive Coupling
- 8.2.1, RF Conducted Emissions
- 8.2.2, RF Radiated Emissions

DoD MIL-STD-704F:

- 5.2, AC power characteristics
- 5.3, DC power characteristics
- 5.4, Load characteristics